

SUPER BRUTE FLOOR SAFES




LIFETIME WARRANTY

If your AMSEC Super Brute floor safe is subject of a sledgehammer or pry attack and is forcibly entered, AMSEC will repair or replace the safe with a current production model of comparable value - free of charge.

- Large brass plated dial and black matte finish dial ring with matching handle
- Attractive design offers strong reliable welds to protect against burglary attacks and reduce possible leakage, with black textured body and door
- UL listed group II key changeable lock, with relock and 1 million possible combinations
- An additional spring-loaded relocking device, activated by a punching attack
- Lock and relocks are protected by a large carburized hardplate
- A handle activated locking mechanism consisting of three 1" diameter locking bolts, each one is drive resistant, chromed steel with a long throw
- One piece heavy duty dead bar behind hinge prevents removal of door even if hinges are removed during a forced entry attempt
- Oversize floor plate ensures strong installation in concrete
- Flush cover plate
- Solid steel hinge mechanism using 3/8" diameter steel hinge pins and internal mounting bolts
- Door jamb design is manufactured with state-of-the-art equipment, with built-in devices offering the ultimate protection against sledgehammer attack
- "B+" rate door: 3/4" solid steel plate door is standard
- Doors are removable and interchangeable within product group; end user can get combination changes by just bringing the door to a locksmith

MFG #	INSIDE DIMENSION	OUTSIDE DIMENSION	CLEAR DOOR	CAPACITY	WEIGHT (LBS)	EZ #
B1500	12-1/4" x 13-1/4" x 8-3/4"	12-3/4" x 14-1/8" x 11-3/4"	10-3/4" x 11-1/8"	1,377	102	013400
B2200	12-1/4" x 13-1/4" x 14"	12-3/4" x 14-1/8" x 17-1/2"	10-3/4" x 11-1/8"	2,203	118	013405
B2900	12-1/4" x 13-1/4" x 18-1/4"	12-3/4" x 14-1/8" x 21-3/8"	10-3/4" x 11-1/8"	2,872	134	013409

UL LISTED B RATED FIRE RATED BURGLARY SAFES



- Manipulation resistant, unitized UL group II key changeable lock protected by a revolving carburized hardplate
- Removable dial and drive/drill resistant spindle preventing damage from burglary attack and additional protection from hold-up
- 1-3/4" solid steel door securely locked by 3 bolts, each requiring over 25,000 pounds to shear, each locking bolt has its own hardened steel positive relocking bolt
- Body: Heavy "B" rated construction
- Water resistant, high impact molded dust cover with rubber "O" ring seal does not rattle or slide like most covers
- STAR's double compartment models provide the commercial user with the most effective cash handling system available, hold-up as well as burglary protection is greatly enhanced by use of this type of safe
- Optional dual key inner compartment available by special order
- **C5S & C7S:** Slotted for depository

When properly installed in concrete, STAR® FLOOR SAFES provide maximum fire and burglary protection.

MFG #	INSIDE DIMENSION	OUTSIDE DIMENSION	CLEAR DOOR	CAPACITY (CU. IN.)	WEIGHT (LBS)	EZ #
C3	8-1/4" diameter x 5-3/4"	8-3/4" diameter x 9"	7-1/4" diameter	280	40	013372
C5	8-1/4" diameter x 10"	8-3/4" diameter x 13-1/2"	7-1/4" diameter	510	46	013374
C5S	8-1/4" diameter x 10"	8-3/4" diameter x 13-1/2"	7-1/4" diameter	510	46	013375
C7	8-1/4" diameter x 16"	8-3/4" diameter x 19"	7-1/4" diameter	785	55	013376
C7S	8-1/4" diameter x 16"	8-3/4" diameter x 19"	7-1/4" diameter	785	55	013377