



www.greensoxsiltfilters.com

Phone: 402-253-2761



12-Green Sox Heavy Duty

Construction		Tubular Knit	
Chemical Reaction	Excellent Resistance to concentrated acids and alkalis		
Properties	Fiber Material	Polyester HDPE	
	Filament Count	60-120	
	Color	Black	
	Melting Point	166°C	330° F
	UV Protection	Biodegradable/UV Stabilized	
	UV Resistance ASTM D4355	150 hours 91.9% 300 hours 83.3% 500 hours 71.6%	
	Approx. Life Expectancy*	18-24 Months	
	Specific Gravity	.91g	
Roll Properties (approx.)	Roll Weight	18.2kg	40lbs
	Roll Length Relaxed	158m	520ft
Applied Roll Length (approx.)	12" Diameter	143m	480ft
Strength Properties	Static Puncture 50mm ASTM D6241	2400 N	
Packaging	Package Type	Roll	

Weights and packaging may vary slightly in different production runs.

Green Sox Silt Filters can be shipped individually or combined on a pallet.

*Life expectancy will vary with your type of application, region and local climactic conditions and should be used as a guide only.

All information supplied is considered to be true and accurate. Any non-standard condition that may affect the application of the fabrics should be consulted with Green Sox.

www.greensoxsiltfilters.com

Phone: 402-253-2761

Fax: 888-594-0141

Info @[greensoxsiltfilters.com](mailto:info@greensoxsiltfilters.com)