
EVOSAFE-SERIES™

ULTRA LOW TEMPERATURE FREEZER
TEMPERATURE RANGE UP TO -86°C
244 LITERS

UPRIGHT FREEZER TYPE VF240-86






Side Front Top Interior

FREEZER TYPE	VF240-86
Internal dimensions (length x depth x height)	450 x 488 x 1111mm
External dimensions (length x depth x height)	755 x 740 x 1832 mm
Minimal transport dimensions (doors, elevators, corners)	700 x 740 x 1822 mm
Net weight	245 kg
Shipping details:	
Transport weight	330 kg
Transport volume	1,88 m^3
Transport dimensions (packed)	940 x 940 x 2130 mm


ACCESSORIES INVENTORY SYSTEMS

ALUMINIUM RACK (incl. drawers with grip) for: 50 mm/ 2” boxes.

article	comp. per freezer	total racks	drawers per rack	boxes per rack	total boxes	max. box height
DSA-4603-136GE	4	12	4	12	144	60
DSA-9573-136GE	2	6	9	27	162	57




DSA-4603-136GE




DSA-9573-136GE

ALUMINIUM RACK (incl. drawers with grip) for: 75 mm/ 3” boxes.

article	comp. per freezer	total racks	drawers per rack	boxes per rack	total boxes	max. box height
DSA-3813-136GE	4	12	3	9	108	81
DSA-6833-136GE	2	6	6	18	108	83



DSA-3813-136GE




DSA-6833-136GE


STAINLESS STEEL RACK (with grips) for: 50 mm/ 2” and 75 mm/ 3” boxes.

article	comp. per freezer	total racks	boxes per rack	total boxes	max. box height
HR-3-4-53E	4	12	12/ 2”	144/ 2”	53
HR-3-3-76E	4	12	9/ 3”	108/ 3”	76

*Specifications subject to change



HR-3-4-53E



HR-3-3-76E

OPTIONS

CO$_2$ BACK-UP SYSTEM
Back-up cooling system.

TEMPERATURE RECORDER
7-days/ 24 hours midi chart recorder, incl. chart paper, pen tip and battery.

NOVO
Text-messenger to pre-programmed mobile phones when controller gives an alarm.

COMMUNICATION BY IFREEZE
Three di erent ways to communicate with the freezer.
1 Through USB-port.
2. Via a local network (Ethernet).
3. Via Internet/ webpage TCP/ IP address.

SNIJDERS LABS

Office and Production
Laurent Janssensstraat 105
5048 AR Tilburg
The Netherlands

Showroom and Testfacility
Gebroeders Salastraat 40
5048 AL Tilburg
The Netherlands

T +31 13 750 15 55
F +31 13 463 86 35
info@snijderslabs.com
www.snijderslabs.com