

FULL MORTISE TEMPLATE BALL BEARING HINGES



- For use on medium weight doors or doors requiring average frequency service
- Ball bearing hinges must be used on doors in conjunction with door closers and on all fire rated openings
- All hinges are ANSI template
- A standard swaging of our standard weight full mortise hinge when closed to parallel position provides a 1-1/16" clearance between leaves
- Size: 4.5" x 4"

BB21

- Non ferrous hinge
- Brass polished and plated

BB51

- Stainless steel polished and satin finish

BB81

- Steel polished and plated or bonderized and prime coated for painting

D

MFG #	DESCRIPTION	FINISH	EZ #
BB21 4.5 4NRP US26D	Non Removeable Pin	Satin Chrome	086566
BB51 4.5 4NRP US32D	Non Removeable Pin	Stainless Steel	086567
BB81 4.5 4NRP US26D	Non Removeable Pin	Satin Chrome	086565
BB81 4.5 4US26D	Removeable Pin	Satin Chrome	086564

FULL MORTISE UL LISTED SPRING HINGE

BHMA
ANSI A156.17
GRADE 1



- Manufactured to close tolerances and meet all specifications and requirements set by ANSI/BHMA A 156.17 Grade 1 and bear UL listed
- A standard swaging of our standard weight full mortise hinge when closed to parallel position provides a 1-1/16" clearance between leaves
- Steel polished and plated or bonderized and prime coated for painting
- Size: 4.5" x 4"

MFG #	FINISH	EZ #
SP81 4.5 4US26D	Satin Chrome	086568

CONCEALED CIRCUIT ELECTRIC HINGE



- An intermediate connector which passes a constant flow of current between the source of power (jamb) and the actuated devices in the door
- 28 gauge multi-strand wire with 12" long leads
- Available with 2 or 4 circuits
- 1 Amp, 24 volts maximum each circuit continuous duty, 16.0 amps intermittent duty (pulse) for 300 milliseconds
- Electric feature undetectable when hinge is installed

MFG #	SIZE	WIRES	EZ #
TA2714CC4 4.5X4 26D	4-1/2" x 4"	4	072882
TA2714CC8 4.5X4 26D	4-1/2" x 4"	8	101403

FULL MORTISE SINGLE ACTING STANDARD WEIGHT SPRING HINGE



- Non handed hinge series has infinite adjustments with the tension being added or reduced by means of provided hex key
- Locking screw provides tamper-resistance after the proper tension has been set
- Nylon tee bearings for vertical and lateral loads
- Coil spring provides closing power
- Steel base material polished and plated

MFG #	SIZE	EZ #
1502 4.5x4.0 26D	4-1/2" x 4"	072883

FIVE KNUCKLE STANDARD WEIGHT SERIES HALF SURFACE PLAIN BEARING HINGE



- Recommended for use on minimum frequency and/or light weight wood or stock hollow metal doors in residences, apartments or other very low frequency doors in commercial construction
- Surface mounted on door, mortised on frame
- Steel base material polished and plated

MFG #	SIZE	EZ #
T2772P	4-1/2" x 4"	080387

M