



**OLD WESTERN PAINT CO., INC**  
**2001 West Barberry Place**  
**Denver, Colorado 80204**

Phone: 303-825-5147/888-765-9827

Fax: 303-825-2437

[www.oldwesternpaint.com](http://www.oldwesternpaint.com)

## PRODUCT INFORMATION

### POLY VAR POLYURETHANE

1255-02 Satin, 1256-04 Velvet, 1257-52 Semi Gloss, 1255-50 Gloss

**TYPE :** One packaged oil modified pure 100% polyurethane.

**DESCRIPTION:** *POLY VAR POLYURETHANE* is a clear, durable interior floor finish available in Gloss, Semi Gloss, Velvet and Satin Sheen. For use on all wood floors, terracotta tile and concrete floors.

**CLEAN UP:** Mineral Spirits/paint thinner

**APPLICATION:**

Brush, Spray, Wool pads – Stir thoroughly. Surface should be free from dust, dirt, wax, grease, oily residue, peeling paint or any loose substance.

Old Floors - Old floors should be abraded. After abrading, remove all dust by vacuum and tacking. Be sure floor is dry before coating. Apply finish, two or three coats, allowing to dry between coats and abrading between coats.

New Floors – Sand floor thoroughly using NOFMA accepted methods. Remove all dust by vacuum and tacking. Be sure floor is dry before applying 3 coats of finish. Abrade, clean and tack between coats. Finish will adhere to most stains and finishes with proper preparation and complete drying. However, ALWAYS PREPARE A SAMPLE/TEST AREA TO DETERMINE COMPATABILITY.

**SPREADING RATE:** Theoretical coverage 500-550 square feet per gallon, subject to surface porosity, texture and application method.

**DRYING TIME:** Dries in 2-4 hours (dust free), recoat in 12 hours. Drying time may be affected by excessive humidity, low temperature, failure of air movement and thickness of finish.

**ANALYSIS:**

**SOLIDS BY WEIGHT**

1255-02 Satin	42.00%
1256-04 Velvet	42.00%
1257-52 Semi Gloss	49.00%
1255-50 Gloss	50.00%

**SOLIDS BY VOLUME**

1255-02 Satin	34.00%
1256-04 Velvet	34.00%
1257-52 Semi Gloss	41.00%
1255-50 Gloss	43.00%

**SOLVENT TYPE**

Aliphatic

**GLOSS 60 DEGREE**

1255-02 Satin	28-34
1256-04 Velvet	34-40
1257-52 Semi Gloss	64-70
1255-50 Gloss	95-97

**V.O.C. content**

1255-02 Satin	504 grams/liter, 4.20 lbs./gallon
1256-04 Velvet	504 grams/liter, 4.20 lbs./gallon
1257-52 S G	488 grams/liter, 4.07 lbs./gal.
1255-50 Gloss	444 grams/liter, 3.71 lbs./gal.

**Features:**

- ❖ Superior Quality
- ❖ 100% Polyurethane Resin
- ❖ Excellent Flow and Level
- ❖ Made in the U.S.A.

LIMITED WARRANTY if used as directed, including proper application and surface preparation in accordance with label directions, this product is warranted to be free from defect when used for its intended application for a period of one year from the date of purchase. This limited warranty does not apply if the product is mixed with any other ingredient. Buyer assumes all risks of handling. Buyer assumes all risks of handling. Buyer's sole and exclusive remedy with respect to any defective product is replacement of product or refund of the purchase price, at Manufacturer's sole option and only after receipt of proof of purchase. THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND DESIGN. IN NO EVENT SHALL MANUFACTURER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LABOR COST. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.