WIRE

GENERAL PURPOSE PRIMARY WIRE

- **Plastic insulated primary wire is standard for original equipment and replacement on all equipment.**
- **Because of its smooth surface it is ideal for pulling through loom or conduit.**
- **Thermoplastic insulation operates satisfactorily between the extreme temperatures of -30F and +176F.**
- **It is highly resistant to grease, oil, and acids and is available in bright colors for easy identification.**
- **For use on 60 volts or less. Meets SAE J1128 specifications. RoHS compliant.**



100 FOOT ROLLS

COLOR	8 GA	10 GA	12 GA	14 GA	16 GA	18 GA	20 GA
BLUE		22543	22550	22557	22564	22571	22600
YELLOW		22544	22551	22558	22565	22572	22601
RED	22599	22549	22556	22563	22570	22577	22602
BLACK	22598	22545	22552	22559	22566	22573	22603
GREEN		22546	22553	22560	22567	22574	22604
WHITE		22547	22554	22561	22568	22575	22605
BROWN		22548	22555	22562	22569	22576	22606
ORANGE				22584	22588		
PURPLE				22585*	22589*		

***** Purple wire rated at 221F.

WIRE STORAGE RACK - PAGE 2006

1000 FOOT ROLLS

COLOR	8 GA	10 GA	12 GA	14 GA	16 GA	18 GA
BLUE				40920		
YELLOW				40921		
BLACK				40922	39356	
GREEN				40923		
WHITE				40924		
BROWN				40925		
RED				40926	39360	

WIRE TERMINALS

NYLON SOLDERLESS TERMINALS

Nylon Insulated Support Sleeve

22-18 Wire Range (Red)

- **Reinforced butted seam with funnel entry.**
- **Vibration resistant with high temperature range.**

J&B #	QTY	STUD SIZE	
21888	50	4-6	
21889	50	4-6	
41240 21891	100 50	8-10 8-10	
21897	25	8-10	
21895	25	4-6	
21900 21901	25 25	4-6 8-10	
41244 21903	100 50	BUTT BUTT	
24763 39183	50 25	F-QUICK 3/16 1/4	
24764 39184	50 25	M-QUICK 3/16 1/4	
45708	25	16-14 to 22-18 STEP DOWN	

WIRE TERMINALS

NYLON SOLDERLESS TERMINALS

Nylon Insulated Support Sleeve

16-14 Wire Range (Blue)

- **Reinforced butted seam with funnel entry.**
- **Vibration resistant with high temperature range.**

J&B #	QTY	STUD SIZE	
21906	50	4-6	
21907	50	4-6	
21908	50	6-8	
41250	100	8-10	
21909	50	8-10	
41251	100	12-1/4	
21910	25	12-1/4	
41252	100	1/4-5/16	
21911	25	1/4-5/16	
21905	25	1/4-5/16	
21912	25	5/16-3/8	
21913	25	4-6	
41256	100	8-10	
21915	25	8-10	
21916	25	4-6	
21920	25	4-6	
41258	100	8-10	
21917	25	8-10	
45708	25	16-14 to 22-18 STEP DOWN	

J&B #	QTY	STUD SIZE	
21918	25	4-6	
21919	25	8-10	
41260	100	BUTT	
21921	50	BUTT	
41264	100	1/4	
21952	25	1/4	
21950	25	1/4	
24766	50	F-QUICK 3/16	
41268	100	1/4	
22291	25	1/4	
24767	50	M-QUICK 3/16	
41269	100	1/4	
22290	25	1/4	
21922	10	3-WAY	
21923	5	4-WAY	
45709	25	12-10 to 16-14 STEP DOWN	

WIRE TERMINALS

NYLON SOLDERLESS TERMINALS

Nylon Insulated Support Sleeve

12-10 Wire Range (Yellow)

- **Reinforced butted seam with funnel entry.**
- **Vibration resistant with high temperature range.**

J&B #	QTY	STUD SIZE	
21924	25	4-6	
21925	25	4-6	
21926	25	6-8	
21927	25	6-8	
41274 21928	100 25	8-10 8-10	
41275 21929	100 25	12-1/4 12-1/4	
21930	25	1/4-5/16	
21931	25	1/4-5/16	
21932	20	5/16-3/8	
21934	10	7/16-1/2	

J&B #	QTY	STUD SIZE	
21939	25	4-6	
21940	25	8-10	
41280 21942	100 25	BUTT BUTT	
21935	25	4-6	
21936	25	8-10	
21937	25	4-6	
21938	25	8-10	
41284 39185	100 25	F-QUICK F-QUICK	
41285 39186	100 25	M-QUICK M-QUICK	
21953	25	1/4	
21951	25	1/4	
45709	25	12-10 to 16-14 STEP DOWN	

WIRE TERMINALS

P.V.C. PLASTIC SOLDERLESS TERMINALS

P.V.C. Plastic Insulating Sleeve

22-18 Wire Range (Red)

- **Butted seam with funnel entry.**

J&B #	QTY	STUD SIZE	
20692	50	4-6	
20693	50	4-6	
24727 20694	100 50	8-10 8-10	
20691	50	12-1/4	
20704	25	5/16	
20624	25	4-6	
20625	25	8-10	
20714	25	4-6	
20715	25	8-10	

J&B #	QTY	STUD SIZE	
20719	25	4-6	
20720	25	8-10	
24746 20735	100 50	BUTT BUTT	
20730	25	1/4	
20729	25	1/4	
21836	10	3-WAY	
21837	5	4-WAY	

WIRE TERMINALS

P.V.C. PLASTIC SOLDERLESS TERMINALS

P.V.C. Plastic Insulating Sleeve

16-14 Wire Range (Blue)

- **Butted seam with funnel entry.**

J&B #	QTY	STUD SIZE	
20695	50	4-6	
20696	50	4-6	
24730 20697	100 50	8-10 8-10	
24731 20698	100 25	12-1/4 12-1/4	
20705	25	3/8	
20626	25	4-6	
24740 20627	100 25	8-10 8-10	
20716	25	4-6	
20717	25	8-10	
20721	25	4-6	

J&B #	QTY	STUD SIZE	
20722	25	8-10	
24747 20736	100 50	BUTT BUTT	
20733	25	3/16	
20734	25	3/16	
24756 20727	100 25	1/4 1/4	
24757 20728	100 25	1/4 1/4	
21838	10	3-WAY	
21839	5	4-WAY	

WIRE TERMINALS

P.V.C. PLASTIC SOLDERLESS TERMINALS

P.V.C. Plastic Insulating Sleeve

12-10 Wire Range (Yellow)

- **Butted seam with funnel entry.**

J&B #	QTY	STUD SIZE	
20706	25	4-6	
24732	100	8-10	
20699	25	8-10	
24733	100	12-1/4	
20700	25	12-1/4	
24734	100	1/4-5/16	
20701	25	1/4-5/16	
24735	100	5/16-3/8	
20702	20	5/16-3/8	
24736	50	7/16-1/2	
20703	15	7/16-1/2	
20628	25	4-6	
24741	100	8-10	
20629	25	8-10	

J&B #	QTY	STUD SIZE	
20718	25	8-10	
20723	25	8-10	
24748	100	BUTT	
20737	25	BUTT	
20731	25	1/4	
20732	25	1/4	
21840	5	3-WAY	
21842	5	4-WAY	

J&B FLEET INDUSTRIAL

WIRE TERMINALS

P.V.C. PLASTIC SOLDERLESS TERMINALS

P.V.C. Plastic Insulating Sleeve

8 Gauge Wire Range (Red)

J&B #	QTY	STUD SIZE	
22004	25	BUTT	
41210	25	8-10	
41212	25	12-1/4	
22000	20	5/16-3/8	
22002	15	7/16-1/2	

WIRE TERMINALS

P.V.C. PLASTIC SOLDERLESS TERMINALS

P.V.C. Plastic Insulating Sleeve

6 Gauge Wire Range (Blue)

J&B #	QTY	STUD SIZE	
41214	15	BUTT	
41218	25	8-10	
41219	25	12-1/4	
41220	25	1/4-5/16	
41221	20	5/16-3/8	
41223	15	7/16-1/2	

P.V.C. PLASTIC SOLDERLESS TERMINALS

P.V.C. Plastic Insulating Sleeve

4 Gauge Wire Range (Yellow)

J&B #	QTY	STUD SIZE	
41226	10	BUTT	
41230	10	12-1/4	
41231	10	1/4-5/16	
41232	10	5/16-3/8	

WIRE TERMINALS

NON-INSULATED SOLDERLESS TERMINALS

Silver Brazed Barrel

- **The brazing allows the terminal to be crimped in any position around the barrel and this also helps give extra wire holding strength.**

22-18 WIRE RANGE			
J&B #	**QTY**	**STUD SIZE**	
39475	100	BUTT	
39490	50	6	
39491	50	10	
39492	50	10	
55914	50	1/4	
55915	50	1/4	

16-14 WIRE RANGE			
J&B #	**QTY**	**STUD SIZE**	
39476	100	BUTT	
39493	50	6	
39494	50	10	
39495	50	1/4	
39489	50	1/4 90° flag	
39497	50	10	
20744	25	8-10 flag	
55903	50	1/4	
55908	50	1/4	

WIRE TERMINALS

NON-INSULATED SOLDERLESS TERMINALS

Silver Brazed Barrel

- **The brazing allows the terminal to be crimped in any position around the barrel and this also helps give extra wire holding strength.**

12-10 WIRE RANGE			
J&B #	**QTY**	**STUD SIZE**	
39477	100	BUTT	
39498	50	10	
39499	50	1/4	
39500	50	5/16	
39501	50	3/8	
39502	50	10	
55901	50	1/4	
55909	50	1/4	

8 GA. WIRE RANGE			
J&B #	**QTY**	**STUD SIZE**	
55897	25	BUTT	
55898	25	10	
55899	25	1/4	
55868	20	3/8	
55869	15	1/2	

WIRE TERMINALS

IN-LINE BUTT CONNECTORS

Join two wires to one



J&B #	WIRE GAUGE	TUBING COLOR	COLOR STRIPE ON CONNECTOR	WIRE	CRIMP DIE (Insulated)	QTY
41902	20-18 AWG	Clear / Red dashes	Side 1 : Red Side 2 : Blue	(1) 20-18 AWG (2) 20-18 AWG	Red (20-18 AWG) Blue (16-14 AWG)	25
41903	16-14 AWG	Clear / Blue dashes	Side 1 : Blue Side 2 : Yellow	(1) 16-14 AWG (2) 16-14 AWG	Blue (16-14 AWG) Yellow (12-10 AWG)	25
41904	12-10 AWG	Clear / Yellow dashes	Side 1 : Yellow Side 2 : Red	(1) 12-10 AWG (2) 12-10 AWG	Yellow (12-10 AWG) Red (8 AWG)	25

CLOSED-END CONNECTORS

Join two to four wires

J&B #	CONNECTOR WIRE RANGE	TUBING COLOR	QTY
41906	22-14 AWG	Clear / Blue dashes	25
41907	18-10 AWG	Clear / Yellow dashes	25

WIRE TERMINALS

KRIMP-N-SEAL CONNECTORS

- **EASY TO SEE:** The clear heat shrink tubing allows the user to see that the stripped wire is properly inserted into the color coded nylon insulated connector. It also ensures that the connector is crimped in the proper place without guess work.
- **STRONG SEAL:** The self sealing tubing encapsulates the connection as sealant inside tubing melts when heat is applied. Seals out corrosion causing moisture and air plus provides strain relief and vibration resistance.
- **SINGLE UNIT CONNECTION:** One complete unit has advantages over other methods. The user no longer has to deal with two separate pieces. This enables a faster installation & ensures heat shrink tubing is applied. The tubing remains permanent & cannot unravel as is the tendency with electrical tape.

WHITE 24-22 GAUGE

J&B #		STUD	QTY
39436		# 4	25
39437		# 6	25
39443		BUTT	25
40405		FORK # 6	25

RED 22-18 GAUGE

J&B #		STUD	QTY
40406		# 8	25
39458		# 10	25
42130		1/4	25
39412		FORK #10	25

STEP DOWN BUTT CONNECTORS

J&B #	GAUGE	QTY
39453	24-22 to 22-18	25

RED 22-18 GAUGE

J&B #		STUD	QTY
39470		BUTT	25
46700			100
40407		F-CONN 3/16 TAB	25
42126		F-CONN 1/4 TAB	25
40408		M-CONN 3/16 TAB	25
42128		M-CONN 1/4 TAB	25
40409		BULLET FEM .157	25
40410		BULLET MALE .157	25
39409		F-CONN 1/4 TAB	25
39410		M-CONN 1/4 TAB	25



Insert stripped end of wire into butt splice.

Crimp splice in nest of tool designed for insulated connectors.

Apply heat source of approximately 275°F to 650°F. Move heat back and forth across tubing until shrinkage occurs. Allow to cool.

WIRE TERMINALS

KRIMP-N-SEAL CONNECTORS

- **EASY TO SEE:** The clear heat shrink tubing allows the user to see that the stripped wire is properly inserted into the color coded nylon insulated connector. It also ensures that the connector is crimped in the proper place without guess work.
- **STRONG SEAL:** The self sealing tubing encapsulates the connection as sealant inside tubing melts when heat is applied. Seals out corrosion causing moisture and air plus provides strain relief and vibration resistance.
- **SINGLE UNIT CONNECTION:** One complete unit has advantages over other methods. The user no longer has to deal with two separate pieces. This enables a faster installation and ensures heat shrink tubing is applied. The tubing remains permanent and cannot unravel as is the tendency with electrical tape.

BLUE 16-14 GAUGE			
J&B #		STUD	QTY
39415		#8	25
39462		#10	25
39463		1/4	25
39464		5/16	25
39465		3/8	25
39460		FORK #10	25
39472 46702		BUTT	25 100

STEP DOWN BUTT CONNECTORS		
J&B #	GAUGE	QTY
42123	22-18 to 16-14	25
42124	16-14 to 12-10	25

BLUE 16-14 GAUGE			
J&B #		STUD	QTY
40411		F-CONN 3/16 TAB	25
39454		F-CONN 1/4 TAB	25
40412		M-CONN 3/16 TAB	25
39455		M-CONN 1/4 TAB	25
42136		BULLET FEM .157	25
40414		BULLET FEM .180	25
42134		BULLET MALE .157	25
40413		BULLET MALE .180	25
39408		F-CONN 1/4 TAB	25
39407		M-CONN 1/4 TAB	25



Insert stripped end of wire into butt splice.

Crimp splice in nest of tool designed for insulated connectors.

Apply heat source of approximately 275°F to 650°F. Move heat back and forth across tubing until shrinkage occurs. Allow to cool.

WIRE TERMINALS

KRIMP-N-SEAL CONNECTORS

- **EASY TO SEE:** The clear heat shrink tubing allows the user to see that the stripped wire is properly inserted into the color coded nylon insulated connector. It also ensures that the connector is crimped in the proper place without guess work.
- **STRONG SEAL:** The self sealing tubing encapsulates the connection as sealant inside tubing melts when heat is applied. Seals out corrosion causing moisture and air plus provides strain relief and vibration resistance.
- **SINGLE UNIT CONNECTION:** One complete unit has advantages over other methods. The user no longer has to deal with two separate pieces. This enables a faster installation and ensures heat shrink tubing is applied. The tubing remains permanent and cannot unravel as is the tendency with electrical tape.

YELLOW 12-10 GAUGE			
J&B #		STUD	QTY
39413		#8	25
39466		#10	25
39467		1/4	25
39414		5/16	25
39468		3/8	25
42132		1/2	25
39411		FORK #10	25
39474		BUTT	25
46704			100
39456		F-CONN 1/4 TAB	25
39457		M-CONN 1/4 TAB	25

YELLOW 12-10 GAUGE			
J&B #		STUD	QTY
40415		BULLET FEM .157	25
40416		BULLET MALE .157	25
39406		F-CONN 1/4 TAB	25
39405		M-CONN 1/4 TAB	25

RED #8 GAUGE			
J&B #		STUD	QTY
39439		1/4	25
39440		3/8	25
39441		1/2	25
39438		BUTT	25

STEP DOWN BUTT CONNECTORS		
J&B #	GAUGE	QTY
40443	#8 GA to 12-10	25



Insert stripped end of wire into butt splice.

Crimp splice in nest of tool designed for insulated connectors.

Apply heat source of approximately 275°F to 650°F. Move heat back and forth across tubing until shrinkage occurs. Allow to cool.

WIRE TERMINALS

OPTISEAL CONNECTORS
Sealed Window Crimp Connectors

- Ensures the wire is crimped to connector.
- Ensures the center of crimp barrel is properly crimped.
- Crystal Clear waterproof insulation allows for indisputable inspection of the wire's condition.

J&B #	WIRE	COLOR	QTY
45692	22-18	RED	25
45693	16-14	BLUE	25
45694	12-10	YELLOW	25

Color-Coded Window Butt Connectors:

- Window in center of connector ensures that wire is seated properly and that the wire is being crimped to connector.
- Color-coded stripes identify wire gauge size to be used with connector.
- Color-coded stripes also indicate/guide the installer to the proper crimp postiton on the center of the barrel.
- Seamless barrel butt connectors ensure superior crimp performance.
- Wire-stop in butt connectors prevents over-insertion of wire.

Crystal Clear Adhesive-Lined Heat Shrink Tubing:

- Crystal Clear tubing provides optimal clarity for visual inspection.
- Adhesive-lined tubing ensures a waterproof seal.
- Wire gauge imprint simplifies wire size identification.

THERMAL INDICATOR SEALED SOLDER CONNECTORS

- The thermal indicator provides the installer with an additional visual clue of the solder sleeve transforming and flowing into wire strands.
- The most common mistake using solder connectors is not heating the solder enough, creating a cold solder joint (inferior termination). To prevent a cold solder joint, the red dye offers an extra visual cue for the installer to continue applying heat to the solder connector until the red dye disappears from the solder sleeve. This ensures a good solder joint, which maximizes tensile strength and conductivity.
- Red thermal indicator disappears from from solder sleeve when solder has flowed.
- Lead free solder alloy has greater surface tension.
- “No-clean” flux on solder sleeve cleans metals & provides quality solder termination.
- Clear tubing allows optimal visual inspection.
- Stronger adhesive provides stronger seal.

J&B #	GAUGE	TUBING COLOR	QTY
40404	24-22	WHITE	25
40400	22-18	RED	25
40401	16-14	BLUE	25
40402	12-10	YELLOW	25

WIRE TERMINALS

MULTILINK™
Sealed Krimp and Solder Connector

MULTILINK PREVENTS . . .

- **CORROSION -** and corrosion build-up at the connection can cause a drop in current or complete disconnection of the circuit. Electrical tape, the most common means of preventing corrosion, does not provide a moisture proof seal but Multilink takes care of this problem all in one step.
- **VIBRATION -** can cause connectors weakened by corrosion or inadequate strain relief to break off. Elektralink offers strain relief protection far superior to current products.
- **MIS-CONNECTED PARTS -** result from poorly installed connectors. A common problem is faulty connection at installation caused by lack of or excess crimping force.

MULTILINK FEATURES . . .

- **CRIMPED** for maximum reliability, **SOLDERED** for strength and conductivity, and **SEALED** for superior durabilty.
- **AN ADHESIVE LINED SLEEVE -** when the connector is heated to shrink the tubing, the adhesive flows and seals the connection. This gives a superior environmental and moisture proof seal that prevents corrosion.
- **HEAT SHRINKABLE CONSTRUCTION -** the combination of a solder connection and heat shrinkable tubing gives this product excellent long-term vibration resistance and strain relief**.**

J&B #	GAUGE	TUBING COLOR	QTY
45635	22-18	RED	25
45636	16-14	BLUE	25
45637	12-10	YELLOW	25

J&B FLEET INDUSTRIAL

WIRE NUT CONNECTORS

HARD PLASTIC

- **Screws on like a nut and holds firmly with a wiring crushing crimp. Will not fall off, shake off or pull off.**
- **600 volts maximum building wiring; 1000 volts in fixtures and signs.**

25126 Gray | **25127** Blue | **25128** Orange | **25129** Yellow | **25130** Red

J&B #	WIRE RING	MIN	MAX	QTY
25126	22 to 16	1 #20 w/1 #22	2 #16	25
25127	22 to 14	3 #22	3 #16	25
25128	22 to 14	3 #22	2 #14 w/1 #18	25
25129	18 to 10	1 #14 w/1 #18	1 #10 w/1 #14	25
25130	18 to 10	2 #14	4 #12	25

WING HARD PLASTIC

- **Positive bottoming design eliminates ratcheting and loose, unsure connections.**
- **600 V maximum for building wiring; 1000 V maximum in fixtures and signs; temperature rating of 105°C (221°F) maximum.**

25145 Gray | **25146** Blue

J&B #	WIRE RING	MIN	MAX	QTY
25145	18-8	2 #12	3 #10 w/1 #12	25
25146	14-6	1 #10 w/1 #12	1 #6 w/2 #8	25

WIRE NUT CONNECTORS

3M COMBO WIRE NUT

- **Simplifies** selection of the right connector for a wide range of wiring jobs.
- 600 volts maximum building wiring; 1000 volts in fixtures and signs; temperature rating of 105°C (221°F) maximum.
- Orange/blue replaces the orange, blue, and gray style wire nut connectors.
- Red/yellow replaces the red and yellow style wire nut connectors.

41177
Orange / Blue

41178
Red / Yellow

41179
Blue / Grey

J&B #	WIRE RING	MIN	MAX	QTY
41177	22 to 12	2 #22	2 #12	25
41178	18 to 8	2 #18	2 #8	25
41179	14 to 6	4 # 14	2 # 6	25

SAFETY SEALED WATERPROOF WIRE NUT

- Suitable for all wire splices, especially those exposed to condensation, water, vapors or dust.
- One step installation.
- Corrosion proof; reduces risk of fire.
- For use in irrigation, trailers, boats or any standard application.

J&B #	WIRE RING	MIN	MAX	QTY
41176	22 to 8	6 # 22	4 # 12	20

WIRING DEVICES

QUICK SPLICE



- **Two piece quick splice makes insulated tap-in, parallel or pig-tail in seconds without cutting, stripping, taping or soldering.**
- **Resilient "spring" action provides firm, positive grip against vibration.**
- **Insert wires into case and press metal grip down with pliers, then close case cover.**

J&B #	GAUGE	COLOR	QTY	APPLICATION
20787	22-18	RED	50	LOW VOLTAGE
20788	18-14	BLUE	50	LOW VOLTAGE
20790	12-10	YELLOW	50	LOW VOLTAGE

DISCONNECTING T-TAP



- **No stripping is required - place wire to be tapped in locating notch and close with common pliers.**
- **Automotive, accessory, fleet and shop applications.**
- **Tap is FULLY INSULATED and ready to accept J&B #22290 (16-14 wire size).**

J&B #	GAUGE	QTY
20786	18-14	10

3 - WAY CONNECTOR W/ SEALANT

- **Self-stripping connectors for making 2 or 3 wire pigtail connections with a wire range of 22-14 gauge.**
- **No wire stripping is required, simply insert wires and press top down with pliers.**
- **The sealant helps to protect against corrosion due to moisture. Use where a positive connection is required.**

J&B #	GAUGE	QTY
20792	22-14	10

FEMALE FLAG QUICK CONNECTS

- **Fully insulated 90' flag 1/4" push on.**

J&B #	GAUGE	COLOR	QTY
22285	22-18	RED	25
22286	16-14	BLUE	25

WIRE TERMINALS

SNAP PLUGS
(Bullet Connectors)

P.V.C. PLASTIC INSULATED SLEEVE



J&B #	SIZE	RANGE	QTY
20741	.156”	16-14	25
24755	.156”	16-14	100
20743	.180”	16-14	25

NYLON INSULATED SLEEVE

J&B #	SIZE	RANGE	QTY
22065	.156”	22-18	25
22066	.156”	16-14	25

RECEPTACLES

- **Converts wire to snap plug receptacle for quick connection/disconnection.**

NYLON SNAP PLUG RECEPTACLES

J&B #	STYLE	RANGE	QTY
20004	.156”	22-18	25
20003	.156”	16-14	25
20006	.180”	16-14	25

INSULATED SNAP PLUG RECEPTACLE 2-WAY

J&B #	STYLE	QTY
20766	STANDARD	25

- **For use with J&B #20741, 24755 & #22066**

PIN TERMINALS
Nylon Insulated Sleeve

J&B #	RANGE	COLOR	QTY	
20763	22-18	RED	50	
20764	16-14	BLUE	50	
20762	12-10	YELLOW	50	

WIRE TERMINALS

QUICK CONNECTORS

- **Used for parking lights, tail lights and other wiring harness applications on GM cars.**

MALE END **FEMALE END**



20630 **20759** **20746** **20745**

J&B #	STYLE	GAUGE	QTY
20630	SPLIT TAB	16-14	25
20759	HOUSING	16-14	25
20745	SPLIT TAB	16-14	25
20746	HOUSING	16-14	25

* **Terminals should be attached to wire before insertion into housing.**

NYLON CLOSED END CONNECTORS

J&B #	GAUGE	QTY	
20749	16-14	25	
20750	12-10	25	

PIGGY BACK TERMINAL

- **For power block 1/4" tab.**
- **Bent back tab is for extra connection.**

J&B #	GAUGE	QTY	
20765 **Non-insul.**	16-14	25	
41234 **(Plastic)**	16-14	50	

.250 PUSH-ON TERMINAL ADAPTER

Two .250" Male to one .250" Female

J&B #	QTY
41233	50



WIRE TERMINALS

DELPHI PACKARD WEATHER-PACK TERMINALS

- **Locking connectors are sealed against moisture, dust and dirt.**
- **Available in one through six contact configurations.**
- **These nylon connectors are rated from -40 F to +257 F.**
- **The terminals and seals are secured in the connector body with a hinge lock assembly.**
- **Silicone seals must be used with the tin plated brass terminals.**
- **Use the cavity plug for all pin locations not filled with terminals. Rated to 16 volts D.C. and 20 amps maximum.**
- **The tower half connector body comes with a self lubricating silicone seal to reduce the engagement assembly force.**

CABLE SEAL

J&B #	CABLE DIA. MM	GPT WIRE GAUGE	SXL WIRE GAUGE	SEAL COLOR	PACKARD #	QTY
42300	1.70-1.29	-	-	RED	12015899	25
42301	2.80-2.03	18-16	20-18	GREEN	12015323	25
42302	3.49-2.81	14	16	GRAY	12010293	25
42303	4.30-3.45	12	14	BLUE	12015193	25

Ordering Notes

1. **Select connector body style from chart.**
2. **One terminal for each contact location needed.**
3. **Pick cable seal by wire gauge.**
4. **Cavity plugs are required for all unused pin locations.**
5. **Weather-Pack crimping tool must be used to assure a good seal.**

CONNECTOR BODIES



Typical four contact configuration

CONTACTS	J&B# TOWER HALF	PACKARD #	J&B# SHROUD HALF	PACKARD #	QTY
1	42306	12015791	42315	12010996	5
2	42307	12015792	42316	12010973	5
3	42308	12015793	42317	12010717	5
4	42309	12015797	42318	12010974	5
6	42311	12015799	42320	12010975	2

WIRE TERMINALS

DELPHI PACKARD WEATHER-PACK TERMINALS

TERMINALS



WIRE GAUGE	J&B# MALE TERMINAL	PACKARD #	J&B# FEMALE TERMINAL	PACKARD #	QTY
20-18	42330	12089040	42333	12089188	25
16-14	42331	12124582	42334	12124580	25
12-10	42332	12124587	42335	12124581	25

CAVITY PLUG

J&B #	PACKARD #	QTY
42340	12010300	25

REMOVAL TOOL

J&B #	PACKARD #	QTY
42341	12014012	EA

DEUTSCH DT SERIES

DEUTSCH DT SERIES RECEPTACLES

- **The Deutsch DT Series sealed RECEPTACLE HOUSINGS make up half of the complete DT Series system connection.**
- **The Deutsch DT Series RECEPTACLE WEDGES are made from a thermoplastic material for a durable and lasting hold.**
- **The receptacles are designed with thermoplastic housings & silicone rear wire interface seals, which make them extremely durable & able to withstand exposure to moisture & a wide temperature range.**
- **They have an IP68 immersion rating & show no defects after 100 cycles of engagement & disengagement.**
- **Operating temperature -55 degree C to .125 degree C (-67 degree F to 257 degree F).**
- **Accepts size 16 contacts (14-20 ga., 13 amps). Integrated latch for mating.**

57100
2-way

57104
3-way

57108
4-way

57112
6-way

57116
8-way

57120
12-way

57101
2-way

57105
3-way

57109
4-way

57113
6-way

57117
8-way

57121
12-way

To complete a receptacle assembly, you will need;
1 receptacle housing.
1 receptacle wedge.
2,3,4,6,8 or 12 receptacle pin contacts.

57125 Pin Contact
57127 Pin Contact

57124 Sealing Plug used to plug any open or unused pin or socket contacts.

J&B #	HOUSING	J&B #	WEDGE	QTY
57100	2-WAY	**57101**	2-WAY	EA
57104	3-WAY	**57105**	3-WAY	EA
57108	4-WAY	**57109**	4-WAY	EA
57112	6-WAY	**57113**	6-WAY	EA
57116	8-WAY	**57117**	8-WAY	EA
57120	12-WAY	**57121**	12-WAY	EA

J&B #	DESCRIPTION	QTY
57125	20-16 Ga. Pin	50
57127	14 Ga. Pin	50
57124	Sealing Plug	50

**** Pins are nickel plated solid barrel**

DEUTSCH DT SERIES

DEUTSCH DT SERIES PLUGS

- **The Deutsch DT Series sealed PLUG HOUSINGS make up half of the complete DT Series system connection.**
- **The Deutsch DT Series PLUG WEDGES are made from a thermoplastic material for a durable and lasting hold.**
- **The plugs are designed with thermoplastic housings & silicone rear wire interface seals, which make them extremely durable & able to withstand exposure to moisture & a wide temperature range.**
- **They have an IP68 immersion rating & show no defects after 100 cycles of engagement & disengagement.**
- **Operating temperature -55 degree C to .125 degree C (-67 degree F to 257 degree F).**
- **Accepts size 16 contacts (14-20 ga., 13 amps). Integrated latch for mating.**

57102
2-way

57106
3-way

57110
4-way

57114
6-way

57118
8-way

57122
12-way

57103
2-way

57107
3-way

57111
4-way

57115
6-way

57119
8-way

57123
12-way

To complete a plug assembly, you will need;
1 plug housing.
1 plug wedge.
2,3,4,6,8 or 12 plug socket contacts.

57126 Socket Contact
57128 Socket Contact

57124 Sealing Plug used to plug any open or unused pin or socket contacts.

J&B #	HOUSING	J&B #	WEDGE	QTY
57102	2-WAY	**57103**	2-WAY	EA
57106	3-WAY	**57107**	3-WAY	EA
57110	4-WAY	**57111**	4-WAY	EA
57114	6-WAY	**57115**	6-WAY	EA
57118	8-WAY	**57119**	8-WAY	EA
57122	12-WAY	**57123**	12-WAY	EA

J&B #	DESCRIPTION	QTY
57126	20-16 Ga. Socket	50
57128	14 Ga. Socket	50
57124	Sealing Plug	50

**** Sockets are nickel plated solid barrel**

DEUTSCH SERIES

DEUTSCH SERIES REMOVAL TOOL

- **The Deutsch multi-use removal tool has a small hook on one end for wedgelock removal and a small screwdriver on the other end for contact removal, pushing back the locking fingers to release the contact.**
- **It is for use with the Deutsch DT, DTM and DTP series.**

J&B #	QTY
57129	EA

DEUTSCH SERIES REMOVAL TOOL
Size 16 Contacts

- **Deutsch contact removal tools are specific to contact size and are used for contact removal in connectors that utilize a round shoulder contact retention system.**
- **They are required for wire removal in the DTHD and Jiffy splice series.**
- **Compact and easy to use. Heavy duty plactic construction.**
- **Removes contacts wihout damaging wire, insulation, connector seals, or connector bodies.**
- **Use with Deutsch Jiffy splice.**

J&B #	QTY
57130	EA

DEUTSCH SERIES JIFFY SPLICE
Size 16

- **Deutsch jiffy splices are a unique, field-servicable alternative to permanent splices.**
- **Inside the body of the jiffy splice is a contact retention system that secures a mated pair of Deutsch contacts in a compact, environmentally sealed unit.**
- **Made from the same high quality silicone elastomer as Deutsch connector seals.**
- **Accepts one size 16 pin and one size 16 socket.**
- **Simple to install and service.**

J&B #	QTY
57131	EA

HEAT SHRINK TUBING

MULTIPLE THICK WALL TUBING

With Meltable Sealant

- **Soft heat shrinkable polyolefin tubing, cross-linked to provide a meltable inner wall.**
- **Outer tubing shrinks and conforms to the geometry to be covered while the inner wall melts and flows to provide environmental protection.**
- **Long term strain relief and greater flexibility which offers less strain at wire/insulation interface; dielectric insulation.**
- **Operates continuously between -50°F and 275°F.**



J&B #	WIRE RANGE	PRE-SHRINK ID	POST SHRINK ID	COLOR	LENGTH	QTY
*57030		1/16	.031	BLACK	6”	10
*57031		3/32	.046	BLACK	6”	10
38750	30-18 GA	1/8”	3/64”	BLACK	6”	4
57050	30-18 GA	1/8”	3/64”	RED	6”	4
38751	20-14 GA	3/16”	1/16”	BLACK	6”	4
57051	20-14 GA	3/16”	1/1/6”	RED	6”	4
38752	18-10 GA	1/4”	3/32”	BLACK	6”	4
57052	18-10 GA	1/4”	3/32”	RED	6”	4
38754	12-16 GA	3/8”	1/8”	BLACK	6”	4
57053	12-16 GA	3/8”	1/8”	RED	6”	4
V38753	2-4/0 GA	1”	5/16”	BLACK	12”	4

*** Part #’s 57030 & 57031 do not have sealant.**

HEAT SHRINK TUBING

MULTIPLE EXTRA THICK WALL TUBING

With Meltable Sealant

- **Semi-rigid heat shrinkable polyolefin tubing, cross-linked to provide a meltable inner wall.**
- **Outer tubing shrinks and conforms to the geometry to be covered while the inner wall melts and flows to provide environmental protection.**
- **Thicker wall provides greater dielectric strength for insulating battery cables and connectors.**
- **Operates continuously from -85°F to +275°F.**



J&B #	WIRE RANGE	PRE SHRINK ID	POST SHRINK ID	COLOR	LENGTH	QTY
21162	18-14 GA	3/8”	.100”	BLACK	6”	4
38660	14-6 GA	1/2”	.150”	BLACK	6”	4
57054	14-6 GA	1/2”	.150”	RED	6”	4
38662	8-1 GA	3/4”	.200”	BLACK	6”	4
40362	8-1 GA	3/4”	.200”	RED	6”	4
38664	2-4/O GA	1”	.370”	BLACK	6”	4
40364	2-4/O GA	1”	.370”	RED	6”	4
60020		1-1/2”	.500”	BLACK	6”	2
60021		2”	.650”	BLACK	6”	2

MULTIPLE WALL TUBING

“Color Coded”

- **Radiation cross-linked, heat shrinkable tubing with meltable adhesive liner.**
- **Superior environmental resistance to mechanical abuse, water, salt, abrasion and other corrosive materials.**
- **Excellent vibration resistance and strain relief.**
- **Rated for continuous operation at temperatures from -55°C (-67°F) to 110°C (+230°F).**



J&B #	WIRE RANGE	PRE SHRINK ID	COLOR	LENGTH	QTY
40979	24-22	1/8”	WHITE	6”	4
40980	22-18	3/16”	RED	6”	4
40981	16-14	1/4”	BLUE	6”	4
40982	12-10	5/16”	YELLOW	6”	4

CABLE TIES

- **Cable ties feature smooth edges and low insertion force.**
- **Locking system assures a firm grip.**
- **Once cable ties are installed, harness assembly won't slip, even after flexing and bending.**
- **Ties are manufactured from 6.6 nylon and are QPL and UL listed.**

J&B #	WIDTH & LENGTH	TENSILE	QTY
38952	3/32 x 4”	18 lb.	100
38955	1/8 x 5”	40 lb.	100
38956	3/16 x 7”	50 lb.	100
38953	3/16 x 11”	50 lb.	100
38957	3/16 x 14”	50 lb.	100
38958	5/16 x 14”	120 lb.	50

BLACK ULTRA VIOLET RESISTANT WIRE TIES

J&B #	WIDTH & LENGTH	TENSILE	QTY
38950	3/32 x 4”	18 lb.	100
38945	1/8 x 5”	40 lb.	100
38959	3/16 x 7”	50 lb.	100
38947	3/16 x 11”	50 lb.	100
38951	3/16 x 14”	50 lb.	100
38949	5/16 x 8.”	120 lb.	100
38954	5/16 x 14”	120 lb.	50
21048	3/8 x 24”	175 lb.	50



J&B #	HOLE	WIDTH & LENGTH	COLOR	TENSILE	QTY
12078	3/16	3/16 x 7”	BLACK	50 lb.	100
12079	3/16	3/16 x 14”	WHITE	50 lb.	25
39005	1/4	5/16 x 15”	BLACK	120 lb.	100

CABLE TIES

RELEASABLE BLACK CABLE TIES

- **Releasable Ties are reusable one piece design, weather resistant black nylon.**
- **Use for prototype work where wires will be added, or when a tie is needed for a temporary application.**

Black Nylon UV Weather Resistant

J&B #	WIDTH & LENGTH	TENSILE	QTY
38946	5/16 x 5.5	50 lb.	100

EXTRA LONG HEAVY DUTY

Black

J&B #	WIDTH & LENGTH	TENSILE	QTY
41186	3/8 x 48	175 lb.	50

CABLE STRAP

- **Black nylon. Fits into 6.3mm (1/4") hole. Import cars.**

J&B #	WIDTH & LENGTH	MAX BUNDLE	QTY
41870	5mm (3/16) x 200mm (8")	44mm (1-3/4")	25

NYLON TIE MOUNTS

J&B #	TYPE	QTY
40025	#6 Screw-On	25
40026	White Adhesive Backing	25
40027	Black Adhesive Backing	25



CABLE TIES

COLORED CABLE TIES

- **Cable ties feature smooth edges and low insertion force; locking system assures firm grip.**
- **Once cable ties are installed, harness assembly won't slip, even after flexing and bending.**
- **Ties are manufactured from 6.6 nylon and are QPL and UL listed.**

J&B #	COLOR	WIDTH & LENGTH	TENSILE	QTY
86120	BROWN	3/32 x 4	18 lb.	100
86121	RED	3/32 x 4	18 lb.	100
86122	ORANGE	3/32 x 4	18 lb.	100
86123	YELLOW	3/32 x 4	18 lb.	100
86124	GREEN	3/32 x 4	18 lb.	100
86125	BLUE	3/32 x 4	18 lb.	100
86126	PURPLE	3/32 x 4	18 lb.	100
86127	NEON PINK	3/32 x 4	18 lb.	100
*86128	MULTIPACK	3/32 x 4	18 lb.	100
41913	BROWN	3/16 x 7-1/2	50 lb.	100
41914	RED	3/16 x 7-1/2	50 lb.	100
41915	ORANGE	3/16 x 7-1/2	50 lb.	100
41916	YELLOW	3/16 x 7-1/2	50 lb.	100
41917	GREEN	3/16 x 7-1/2	50 lb.	100
41918	BLUE	3/16 x 7-1/2	50 lb.	100
41919	PURPLE	3/16 x 7-1/2	50 lb.	100
41921	NEON PINK	3/16 x 7-1/2	50 lb.	100
*41922	MULTIPACK	3/16 x 7-1/2	50 lb.	100

***10 Each of white, black, brown, red, orange, yellow, green, blue, purple & neon pink ties.**

BUTTON HEAD CABLE TIES

- **These button head ties are a two piece tie providing for parallel entry and exit through the head.**
- **The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head.**
- **This design allows the strap to be directed clockwise or counter-clockwise prior to insertion into the head, enabling bi-directional looping.**

J&B #	COLOR	WIDTH & LENGTH	TENSILE	QTY
46448	BLACK	3/16 x 11.8”	100 lb.	50

CABLE TIES

DUAL CLAMP TIES

- High impact heat stabilized nylon material.
- Ensures parallel spacing between cables & hoses; keeps them from rubbing against each other & deteriorating.
- Used in many cars, trucks & trailers where high tensile strength & flexibility is needed.
- Releasable straps. UV resistant. UL listed. RoHs compliant.
- Operating temperature range: -40 deg F to +230 deg F.

J&B #	WIDTH & LENGTH	BUNDLE DIA. MAX. EA SIDE	TENSILE STRENGTH	STUD SIZE	QTY
4300	1/2 x 13”	1.3”	150 lbs.	1/4	10
4305	1/2 x 19”	2.3”	150 lbs.	1/4	10

TREE CLIP CABLE TIES

- Tie strap with Christmas tree style push mount.
- Designed to pass through a pre-drilled hole and Lock into place.
- Also known as black retainer push mount cable tie.

J&B #	LENGTH	TENSILE STRENGTH	HOLE SIZE	QTY
V46118	8”	50 lbs.	1/4	25

WIRE TOOLS

CRIMPING & CUTTING TOOL

- **Cuts and strips wire from 22 to 10 gauge.**
- **Crimps insulated and non-insulated terminals.**
- **Cuts screws from 4-40 up to 10-32.**
- **Assembled with plastic comfort grip handles.**



J&B #	QTY
20772	EA

SELF-ADJUSTING WIRE CUTTER/STRIPPER

- **Unique steel jaws self-adjust to strip any wire 26-10 gauge.**
- **Crimps insulated and non-insulated 22 to 10 gauge and 7mm/8mm terminals.**
- **Precision machined blade for cutting wire sharp and smooth.**



J&B #	QTY
39350	EA

RATCHET CRIMPING TOOL

For Heat Shrink Terminals

- 4 crimp nests - 8, 10-12, 14-16, 18-22.
- Ensures uniform crimp termination regardless of user.
- Release switch if terminal or wire is inserted improperly.
- High quality, economical tool.
- Alignment guide to ensure dies won't slip during crimping.

J&B #	QTY
41209	EA
























J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2011

NYLON TERMINALS

21891 1 (41240) 20 **8-10 RING 22-18**	**21908** 2 20 **6-8 RING 16-14**	**21909** 3 (41250) 15 **8-10 RING 16-14**	**21910** 4 (41251) 10 **12-1/4 RING 16-14**	**21928** 5 (41274) 15 **8-10 RING 12-10**	**20749** 6  10 **CRIMP SPLICE CONNECTOR 16-14**
21911 7 (41252) 10 **1/4-5/16 RING 16-14**	**21912** 8 5 **5/16-3/8 RING 16-14**	**21929** 9 (41275) 10 **12-1/4 RING 12-10**	**21930** 10 10 **1/4 – 5/16 RING 12-10**	**21932** 11 5 **5/16-3/8 RING 12-10**	**20750** 12 10 **CRIMP SPLICE CONNECTOR 12-10**
21934 13 5 **7/16-1/2 RING 12-10**	**21897** 14 10 **8-10 FORK 22-18**	**21915** 15 (41256) 10 **8-10 FORK 16-14**	**21903** 16 (41244) 20 **BUTT CONNECTOR 22-18**	**21921** 17 (41260) 20 **BUTT CONNECTOR 16-14**	**20788** 18 5 **SCOTCHLOK CONNECTOR 18-14**
21942 19 (41280) 15 **BUTT CONNECTOR 12-10**	**21952** 20 (41264) 10 **1/4 MALE 16-14**	**21950** 21 (41265) 10 **1/4 FEMALE 16-14**	**22216** 22 10 **SPLICING CAP 24-12**	**22066** 23 10 **SNAP PLUG 16-14**	**20003** 24 10 **FEMALE PLUG 16-14**



J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2213

NYLON TERMINALS

1 **21942** (41280) 12-10 BUTT CONNECTOR 10	2 **21928** (41274) 8-10 RING 12-10 10	3 **21921** (41260) 16-14 BUTT CONNECTOR 10	4 **21909** (41250) 8-10 RING 16-14 10	5 **21903** (41244) 22-18 BUTT CONNECTOR 10	6 **39184** 22-18 MALE DISCONNECT 10
7 **21934** 7/16-1/2 RING 12-10 10	8 **39185** (41284) FEMALE DISCONNECT 12-10 10	9 **21912** 5/16-3/8 RING 16-14 10	10 **22291** (41268) FEMALE DISCONNECT 16-14 10	11 **21888** 4-6 RING 22-18 10	12 10
13 **21932** 5/16-3/8 RING 12-10 10	14 **39186** (41285) MALE DISCONNECT 12-10 10	15 **21911** (41252) 1/4-5/16 RING 16-14 10	16 **22290** (41269) MALE DISCONNECT 16-14 10	17 **21891** (41240) 8-10 RING 22-18 10	18
19 **21929** (41275) 12-1/4 RING 12-10 10	20	21 **21910** (41251) 12-1/4 RING 16-14 10	22	23 **39183** FEMALE DISCONNECT 22-18 10	24



J&B Fleet - Industrial Supply
22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411
www.jbfleet.com



PART # 2104

NYLON TERMINALS

1 **22291** (41268) FEMALE FULLY INSULATED 5 16-14	2 **22290** (41269) MALE FULLY INSULATED 5 16-14	3 **21950** (41265) 1/4 FEMALE 5 16-14	4 **21952** (41264) 1/4 MALE 5 16-14	5 **20792** 3-WAY CONNECTOR W/SEALANT 3	6 **21901** 8 - 10 FORK 5 22-18	7 **21891** (41240) 8 - 10 RING 3 22-18	8 **21903** (41244) BUTT CONNECT 10 22-18
9 **22066** MALE SNAP PLUG 3 16-14	10 **21917** (41258) 8 - 10 FORK 3 16 - 14	11 **21912** 3/8 RING 3 16-14	12 **21911** (41252) 5/16 RING 3 16-14	13 **21910** (41251) 1/4 RING 5 16-14	14 **21909** (41250) 8 - 10 RING 5 16-14	15 **21907** 6-8 RING 5 16-14	16 **21921** (41260) BUTT CONNECT 10 16-14
17 **20003** FEMALE RECEPTACLE 3 16-14	18 **21938** 8 - 10 FORK 3 12-10	19 **21934** 1/2 RING 2 12-10	20 **21932** 3/8 RING 3 12-10	21 **21930** 5/16 RING 3 12-10	22 **21929** (41275) 1/4 RING 5 12-10	23 **21928** (41274) 8 - 10 RING 10 12-10	24 **21942** (41280) BUTT CONNECT 10 12-10
25 **39185** (41284) FEMALE FULLY INSULATED 3 12-10	26 **39186** (41285) MALE FULLY INSULATED 3 12-10	27 **21951** 1/4 FEMALE 3 12-10	28 **21953** 1/4 MALE 3 12-10	29	30	31 **20788**  SCOTCHLOK 5 18 - 14	32 **20786**  T – TAP 3 18 - 14

LET US HELP YOU MAKE THE CONNECTION

PART # 3000

NYLON TERMINALS

J & B FLEET-INDUSTRIAL SUPPLY
PHONE: 330-821-6342

21891 **8-10 RING** **22-18** 10	**21909** **8-10 RING** **16-14** 10	**21910** **12-1/4 RING** **16-14** 10	**21911** **1/4-5/16 RING** **16-14** 10	**21912** **5/16-3/8 RING** **16-14** 10	**21928** **8-10 RING** **12-10** 10
21929 **12-1/4 RING** **12-10** 10	**21930** **1/4-5/16 RING** **12-10** 10	**21932** **5/16-3/8 RING** **12-10** 10	**21934** **7/16-1/2 RING** **12-10** 10	**21952** **1/4 MALE** **16-14** 10	**21950** **1/4 FEMALE** **16-14** 10
21903 **BUTT CONN** **22-18** 10	**21921** **BUTT CONN** **16-14** 10	**21942** **BUTT CONN** **12-10** 10	**22066** **SNAP PLUG** **16-14** 10	**20003** **FEMALE PLUG** **16-14** 10	**21915** **8-10 FORK** **16-14** 10

J&B Fleet - Industrial Supply
22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411
www.jbfleet.com

PART # 2133

PLASTIC & NYLON TERMINALS

1 **22291** (41268) NYLON FEMALE FULLY INSUL 5 16-14	2 **22290** (41269) NYLON MALE FULLY INSUL 5 16-14	3 **20728** (24757) PLASTIC FEMALE 5 16-14	4 **20727** (24756) PLASTIC MALE 5 16-14	5 **20792** 3-WAY CONNECTOR W/SEALANT 3	6 **21901** NYLON 8-10 FORK 22-18 5	7 **20694** (24727) PLASTIC 8-10 RING 22-18 3	8 **21903** (41244) NYLON BUTT CONNECT 22-18 10
9 **22066** MALE SNAP PLUG 16-14 3	10 **21917** (41258)  NYLON 8-10 FORK 16-14 3	11 **20705** PLASTIC 3/8 RING 16-14 3	12 **21911** (41252) NYLON 5/16 RING 16-14 3	13 **20698** (24731) PLASTIC 1/4 RING 16-14 5	14 **20697** (24730) PLASTIC 8-10 RING 16-14 5	15 **20696** (24729) PLASTIC 6-8 RING 16-14 5	16 **21921** (41260) NYLON BUTT CONNECT 16-14 10
17 **20003** FEMALE RECEPTACLE 16-14 3	18 **21938** NYLON 8-10 FORK 12-10 3	19 **20703** (24726) PLASTIC 1/2 RING 12-10 2	20 **20702** (24735) PLASTIC 3/8 RING 12-10 3	21 **20701** (24734) PLASTIC 5/16 RING 12-10 3	22 **20700** (24733) PLASTIC 1/4 RING 12-10 5	23 **20699** (24732) PLASTIC 8-10 RING 12-10 10	24 **21942** (41280) NYLON BUTT CONNECT 12-10 10
25 **41284** NYLON FEMALE FULLY INSUL 3 12-10	26 **41285** NYLON MALE FULLY INSUL 3 12-10	27 **20732** PLASTIC FEMALE 3 12-10	28 **20731** PLASTIC MALE 3 12-10	29	30	31 **20788**  SCOTCHLOCK 18-14 5	32 **20786**  T – TAP 18-14 3

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2192

PLASTIC TERMINALS

1	2 **41210** 8-10 RING 5 #8 GAUGE	3 **41212** 12-1/4 RING 5 #8 GAUGE	4	5 **22000** 5/16-3/8 RING 5 #8 GAUGE	6 **22002** 7/16-1/2 RING 5 #8 GAUGE
7	8	9	10	11	12 **22004** # 8 GA BUTT CONNECTOR 10
13 **41218** 8-10 RING 5 #6 GAUGE	14 **41219** 12-1/4 RING 5 #6 GAUGE	15 **41220** 1/4-5/16 RING 5 #6 GAUGE	16 **41221** 5/16-3/8 RING 5 #6 GAUGE	17 **41223** 7/16-1/2 RING 5 #6 GAUGE	18 **41214** # 6 GA BUTT CONNECTOR 5
19 **41230** 12-1/4 RING 3 #4 GAUGE	20 **41231** 1/4-5/16 RING 3 #4 GAUGE	21 **41232** 5/16-3/8 RING 3 #4 GAUGE	22	23	24 **41226** # 4 GA BUTT CONNECTOR 5

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2049

PLASTIC TERMINALS

1 **20694** (24727) 15 **8-10 RING 22-18**	2 **20696** (24729) 15 **4-6 RING 16-14**	3 **20697** (24730) 25 **8-10 RING 16-14**	4 **20698** (24731) 10 **12-1/4 RING 16-14**	5 **20699** (24732) 25 **8-10 RING 12-10**	6 **25127** 10 **WIRE NUT CONNECTOR BLUE**
7 **20700** (24733) 10 **12-1/4 RING 12-10**	8 **20701** (24734) 10 **1/4-5/16 RING 12-10**	9 **20702** (24735) 10 **5/16-3/8 RING 12-10**	10 **20703** (24736) 5 **7/16-1/2 RING 12-10**	11 **20629** (24741) 25 **8-10 FORK 12-10**	12 **25128** 10 **WIRE NUT CONNECTOR ORANGE**
13 **20792** 3 **3-WAY CONNECTOR W/ SEALANT**	14 **20625** (24738) 10 **8-10 FORK 22-18**	15 **20627** (24740) 25 **8-10 FORK 16-14**	16 **20735** (24746) 25 **BUTT CONNECTOR 22-18**	17 **20736** (24747) 25 **BUTT CONNECTOR 16-14**	18 **25129** 10 **WIRE NUT CONNECTOR YELLOW**
19 **20737** (24748) 25 **BUTT CONNECTOR 12-10**	20 **20728** (24757) 25 **1/4 FEMALE 16-14**	21 **20727** (24756) 25 **1/4 MALE 16-14**	22 **20003** 10 **FEMALE PLUG 16-14**	23 **20741** (24755) 10 **SNAP PLUG 16-14**	24 **20788** 10 **SCOTCHLOK CONNECTOR 18-14**

LET US HELP YOU MAKE THE CONNECTION

PART # 3001

PLASTIC TERMINALS

J & B FLEET-INDUSTRIAL SUPPLY
PHONE: 330-821-6342

20694 **8-10 RING** **22-18** 10	**20697** **8-10 RING** **16-14** 10	**20698** **12 - 1/4 RING** **16-14** 10	**20705** **3/8 RING** **16-14** 10	**20629** **8-10 FORK** **12-10** 10	**20699** **8-10 RING** **12-10** 10
20700 **12 - 1/4 RING** **12-10** 10	**20701** **1/4 - 5/16 RING** **12-10** 10	**20702** **5/16 - 3/8 RING** **12-10** 10	**20703** **7/16 - 1/2 RING** **12-10** 10	**20727** **1/4 MALE** **16-14** 10	**20728** **1/4 FEMALE** **16-14** 10
20735 **BUTT CONN** **22-18** 10	**20736** **BUTT CONN** **16-14** 10	**20737** **BUTT CONN** **12-10** 10	**20741** **SNAP PLUG** **16-14** 10	**20003** **FEMALE PLUG** **16-14** 10	**20627** **8-10 FORK** **16-14** 10

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2224

NON-INSULATED TERMINALS

39475 1 **22-18 BUTT CONNECTOR** 25	**39490** 2 **22-18 # 6 RING** 25	**39491** 3 **22-18 # 10 RING** 25	**39492** 4 **22-18 # 10 FORK** 25	**20744** 5 **16-14 8-10 FLAG** 10	6	**55914** 7 **22-18 FEMALE 1/4 STUD** 25	**55915** 8 **22-18 MALE 1/4 STUD** 25
39476 9 **16-14 BUTT CONNECTOR** 25	**39493** 10 **16-14 # 6 RING** 25	**39494** 11 **16-14 # 10 RING** 25	**39495** 12 **16-14 1/4 RING** 25	**39489** 13 **16-14 1/4 90 FLAG** 10	**39497** 14 **16-14 # 10 FORK** 10	**55903** 15 **16-14 FEMALE 1/4 STUD** 25	**55908** 16 **16-14 MALE 1/4 STUD** 25
39477 17 **12-10 BUTT CONNECTOR** 25	**39498** 18 **12-10 # 10 RING** 25	**39499** 19 **12-10 1/4 RING** 25	**39500** 20 **12-10 5/16 RING** 10	**39501** 21 **12-10 3/8 RING** 10	**39502** 22 **12-10 # 10 FORK** 25	**55901** 23 **12-10 FEMALE 1/4 STUD** 25	**55909** 24 **12-10 MALE 1/4 STUD** 25
55897 25 **8 GA BUTT CONNECTOR** 10	**55898** 26 **8 GA # 10 RING** 10	**55899** 27 **8 GA 1/4 RING** 10	**55868** 28 **8 GA 3/8 RING** 10	**55869** 29 **8 GA 1/2 RING** 10	30	31	32



J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

SEALED MULTIPLE WIRE CONNECTORS

PART # 2235

41902 1 **20-18 AWG** **2-1 IN LINE BUTT** **CONNECTOR** 5	**41903** 2 **16-14 AWG** **2-1 IN LINE BUTT** **CONNECTOR** 5	**41904** 3 **12-10 AWG** **2-1 IN LINE BUTT** **CONNECTOR** 5
4	5	6
41906 7 **22-14 AWG** **CLOSED END** 5	**41907** 8 **18-10 AWG** **CLOSED END** 5	**20792** 9 **3- WAY CONNECTOR** **W/SEALANT** 5
10	11	12



J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2211

SHRINK TERMINALS

1 **39474** 10 12-10 GA BUTT CONNECTOR	2 **39466** 10 12-10 GA 8-10 STUD	3 **39472** 10 16-14 GA BUTT CONNECTOR	4 **39462** 10 16-14 GA 8-10 STUD	5 **39470** 10 22-18 GA BUTT CONNECTOR	6 **42126** 5 22-18 GA FEMALE CONNECTOR
7 **42132** 5 12-10 GA 1/2 STUD	8 **39456** 5 12-10 GA FEMALE CONNECTOR	9 **39465** 5 16-14 GA 5/16-3/8 STUD	10 **39455** 5 16-14 GA MALE CONNECTOR	11 **42130** 10 22-18 1/4 STUD	12
13 **39468** 5 12-10 GA 5/16-3/8 STUD	14 **39457** 5 12-10 GA MALE CONNECTOR	15 **39464** 10 16-14 GA 5/16 STUD	16 **39454** 5 16-14 GA FEMALE CONNECTOR	17 **39458** 10 22-18 GA 8-10 STUD	18
19 **39467** 10 12-10 GA 12-1/4 STUD	20 **41907** 5 18-10 AWG CLOSED-END CONNECTOR	21 **39463** 10 16-14 GA 12-1/4 STUD	22 **41906** 5 22-14 AWG CLOSED-END CONNECTOR	23 **42128** 5 22-18 GA MALE CONNECTOR	24

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2895

SHRINK TERMINALS – RINGS / BULLETS / FORKS

39436 1 5 24-22 GA #4 RING	39437 2 5 24-22 GA #6 RING	40406 3 5 22-18 GA #8 RING	39458 4 5 22-18 GA #10 RING	42130 5 5 22-18 GA 1/4 RING	39415 6 5 16-14 GA #8 RING	39462 7 5 16-14 GA #10 RING	39463 8 5 16-14 GA 1/4 RING
39464 9 5 16-14 GA 5/16 RING	39465 10 5 16-14 GA 3/8 RING	39413 11 5 12-10 GA #8 RING	39466 12 5 16-14 GA #10 RING	39467 13 5 16-14 GA 1/4 RING	39414 14 5 16-14 GA 5/16 RING	39468 15 5 16-14 GA 3/8 RING	42132 16 5 16-14 GA 1/2 RING
39439 17 3 #8 GA 1/4 RING	39440 18 3 #8 GA 3/8 RING	39441 19 3 #8 GA 1/2 RING	40405 20 5 24-22 GA #6 FORK	39412 21 5 22-18 GA #10 FORK	39460 22 5 16-14 GA #10 FORK	39411 23 5 12-10 GA #10 FORK	24
40409 25 5 22-18 GA .157 FEMALE BULLET	40410 26 5 22-18 GA .157 MALE BULLET	42136 27 5 16-14 GA .157 FEMALE BULLET	42134 28 5 16-14 GA .157 MALE BULLET	40414 29 5 16-14 GA .180 FEMALE BULLET	40413 30 5 16-14 GA .180 MALE BULLET	40415 31 5 12-10 GA .157 FEMALE BULLET	40416 32 5 12-10 GA .157 MALE BULLET

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2896

SHRINK TERMINALS – BUTTS / STEPS / QUICK CONNECTS

40407 1 22-18 GA 3/16 TAB 5 FEM CONN.	**40408** 2 22-18 GA 3/16 TAB 5 MALE CONN.	**42126** 3 22-18 GA 1/4 TAB 5 FEM CONN.	**42128** 4 22-18 GA 1/4 TAB 5 MALE CONN.	**39409** 5 22-18 GA 1/4 TAB 5 FEM CONN.	**39410** 6 22-18 GA 1/4 TAB 5 MALE CONN.	**40411** 7 16-14 GA 3/16 TAB 5 FEM CONN.	**40412** 8 16-14 GA 3/16 TAB 5 MALE CONN.
39454 9 16-14 GA 1/4 TAB 5 FEM CONN.	**39455** 10 16-14 GA 1/4 TAB 5 MALE CONN.	**39408** 11 16-14 GA 1/4 TAB 5 FEM CONN.	**39407** 12 16-14 GA 1/4 TAB 5 MALE CONN.	**39456** 13 12-10 GA 1/4 TAB 5 FEM CONN.	**39457** 14 12-10 GA 1/4 TAB 5 MALE CONN.	**39406** 15 12-10 GA 1/4 TAB 5 FEM CONN.	**39405** 16 12-10 GA 1/4 TAB 5 MALE CONN.
39443 17 46700 24-22 GA 5 BUTT CONN.	**39470** 18 22-18 GA 10 BUTT CONN.	19	**39472** 20 46702 16-14 GA 10 BUTT CONN.	21	**39474** 22 46704 12-10 GA 10 BUTT CONN.	23	**39438** 24 #8 GA 3 BUTT CONN.
39453 25 24-22 TO 22-18 5 STEP DOWN	**42123** 26 22-18 TO 16-14 5 STEP DOWN	27	**42124** 28 16-14 TO 12-10 5 STEP DOWN	29	**40443** 30 12-10 TO #8 3 STEP DOWN	31	32

LET US HELP YOU MAKE THE CONNECTION

PART # 3002

SHRINK TERMINALS

J & B FLEET-INDUSTRIAL SUPPLY
PHONE: 330-821-6342

39454 **16-14 FEMALE CONNECTOR** 5	**39455** **16-14 MALE CONNECTOR** 5	**39470** **22-18 BUTT CONNECTOR** 5	**39472** **16-14 BUTT CONNECTOR** 5	**39474** **12-10 BUTT CONNECTOR** 5	
39458 **8-10 RING 22-18** 5	**39462** **8-10 RING 16-14** 5	**39463** **1/4 RING 16-14** 5	**39466** **8-10 RING 12-10** 5	**39467** **1/4 RING 12-10** 5	**39468** **3/8 RING 12-10** 5

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2134

SHRINK TERMINALS

1 **42126**  **22-18 FEMALE** 5	2 **42128** **22-18 MALE** 5	3 **42130** **22-18 1/4 RING** 5	4 **39458** **22-18 10 RING** 5	5 **39470** **22-18 BUTT** 10	6 **42123** **STEP DOWN BUTT** **22-18 to 16-14** 5
7 **39465** **16-14 3/8 RING** 5	8 **39464** **16-14 5/16 RING** 5	9 **39463** **16-14 1/4 RING** 5	10 **39462** **16-14 10 RING** 5	11 **39472** **16-14 BUTT** 10	12 **42124** **STEP DOWN BUTT** **16-14 to 12-10** 5
13 **39454**  **16-14 FEMALE** 5	14 **39455** **16-14 MALE** 5	15 **39460** **16-14 10 FORK** 5	16 **39456**  **12-10 FEMALE** 5	17 **39457** **12-10 MALE** 5	18 **42134** **16-14 M BULLET** 5
19 **42132** **12-10 1/2 RING** 5	20 **39468** **12-10 3/8 RING** 5	21 **39467** **12-10 1/4 RING** 5	22 **39466** **12-10 10 RING** 5	23 **39474** **12-10 BUTT** 10	24 **42136** **16-14 F BULLET** 5



J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2228

SHRINK TERMINALS

1 **39443** 22-24GA BUTT CONNECTOR 5	2 **39458** 20-18 GA 8-10 STUD 5	3 **42130** 20-18 GA 1/4 STUD 4	4 **42126** 20-18 GA FEMALE CONNECTOR 4	5 **42128** 20-18 GA MALE CONNECTOR 4	6 **39412** 20-18 GA FORK 5	7 **39470** 20-18 GA BUTT CONNECTOR 5	8 **39415** 16-14 GA 8 STUD 5
9 **39462** 16-14 GA 10 STUD 5	10 **39463** 16-14 GA 1/4 STUD 5	11 **39464** 16-14 GA 5/16 STUD 5	12 **39465** 16-14 GA 3/8 STUD 5	13 **39454** 16-14 GA FEMALE CONNECTOR 5	14 **39455** 16-14 GA MALE CONNECTOR 5	15 **39408** 16-14 GA FEMALE CONNECTOR 5	16 **39407** 16-14 GA MALE CONNECTOR 5
17 **39460** 16-14 GA 8-10 FORK 5	18 **42136** 16-14 GA FEMALE BULLET 5	19 **42134** 16-14 GA MALE BULLET 5	20 **39472** 16-14 GA BUTT CONNECTOR 10	21 **42123** 21-18 TO 16-14 STEP DOWN BUTT CONNECTOR 3	22 **42124** 16-14 TO 12-10 STEP DOWN BUTT CONNECTOR 3	23 **39413** 12-10 GA 8 STUD 5	24 **39466** 12-10 GA 10 STUD 5
25 **39467** 12-10 GA 1/4" STUD 5	26 **39414** 12-10 GA 5/16" STUD 5	27 **39468** 12-10 GA 3/8" STUD 4	28 **42132** 12-10 GA 1/2" STUD 4	29 **39456** 12-10 GA FEMALE CONNECTOR 4	30 **39457** 12-10 GA MALE CONNECTOR 4	31 **39474** 12-10 GA BUTT CONNECTOR 5	32 **39411** 12-10 GA FORK 5





J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2203

WIRE NUTS

1 **25129** 18-10 PLASTIC YELLOW 10	2 **41177**  22-12 COMBO NUT ORANGE/BLUE 10	3 **25146** 14-6 PLASTIC WING BLUE 10	4
5 **25128** 22-14 PLASTIC ORANGE 10	6 **22217** 16-10 SOFT PLASTIC RED 10	7 **25145** 18-8 PLASTIC WING GRAY 10	8
9 **25127** 22-14 PLASTIC BLUE 10	10 **22216** 18-12 SOFT PLASTIC YELLOW 10	11 **41179**  14-6 COMBO NUT BLUE/GREY 5	12
13 **25126** 22-16 PLASTIC GRAY 10	14 **25130** 18-10 PLASTIC RED 10	15 **41178**  18-8 COMBO NUT RED/YELLOW 10	16 **41176** 22-8 SEALED WIRE NUT 5

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2010

DELPHI PACKARD TERMINALS

42308 3 CONTACT TOWER 2	**42317** 3 CONTACT SHROUD 2	**42311** 6 CONTACT TOWER 2	**42320** 6 CONTACT SHROUD 2
42307 2 CONTACT TOWER 2	**42316** 2 CONTACT SHROUD 2	**42309** 4 CONTACT TOWER 2	**42318** 4 CONTACT SHROUD 2
42306 1 CONTACT TOWER 2	**42315** 1 CONTACT SHROUD 2		
42341 REMOVAL TOOL **1**	**42333** 20-18 FEMALE 10	**42334** 16-14 FEMALE 10	**42335** 12 GAUGE FEMALE 10
42340 CAVITY PLUG 10	**42330** 20-18 MALE 10	**42331** 16-14 MALE 10	**42332** 12 GAUGE MALE 10
42300 CABLE DIA MM 1.70-1.29 RED SEAL 10	**42301** CABLE DIA MM 2.80-2.03 GREEN SEAL 10	**42302** CABLE DIA MM 3.49-2.81 GRAY SEAL 10	**42303** CABLE DIA MM 4.30-3.45 BLUE SEAL 10












J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2120

SHRINK TUBING

1	2	3	4
38751 / **57051**	**38754** / **57053**	**38662** / **40362**	**38664** / **40364**
3/16 BLACK / **3/16 RED**	**3/8 BLACK** / **3/8 RED**	**8 – 1 BLACK** / **8 – 1 RED**	**2 – 4/O BLACK** / **2 – 4/O RED**
			
PRE-SHRINK ID .187	**PRE-SHRINK ID .375**	**PRE-SHRINK ID .750**	**PRE-SHRINK ID 1.100**
4 **POST-SHRINK ID .059** 4	4 **POST-SHRINK ID .135** 4	2 **POST-SHRINK ID .250** 2	2 **POST-SHRINK ID .375** 2
38750 / **57050**	**38752** / **57052**	**38660** / **57054**	
1/8 BLACK / **1/8 RED**	**1/4 BLACK** / **1/4 RED**	**14 - 6 BLACK** / **14 - 6 RED**	
PRE-SHRINK ID .125	**PRE-SHRINK ID .250**	**PRE-SHRINK ID .400**	
POST-SHRINK ID .023	**POST-SHRINK ID .080**	**POST-SHRINK ID .150**	
4 4	4 4	2 2	
5	6	7	8

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2390

HEAT SHRINK TUBING

4	38750 1/8 BLACK	57050 1/8 RED	4	2	38662 3/4 BLACK
4	38751 3/16 BLACK	57051 3/16 RED	4	2	40362 3/4 RED
4	38752 1/4 BLACK	57052 1/4 RED	4	1	38664 1” BLACK
4	38754 3/8 BLACK	57053 3/8 RED	4	1	38664 1” BLACK
2	38660 1/2 BLACK			1	40364 1” RED
2	57054 1/2 RED			1	40364 1” RED

LET US HELP YOU MAKE THE CONNECTION

PART # 3003

HEAT SHRINK TUBING

J & B FLEET-INDUSTRIAL SUPPLY
PHONE: 330-821-6342

38750 BLACK	38751 BLACK	38752 BLACK	38754 BLACK	38660 BLACK	57054 RED
1/8"	3/16"	1/4"	3/8"	1/2"	1/2"
57050 RED	57051 RED	57052 RED	57053 RED		
4 4	4 4	2 2	2 2	2	2

J&B Fleet - Industrial Supply
22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411
www.jbfleet.com

PART # 2105

WHITE CABLE TIES

1	**38952**	2	**38955**
25	**3/32 X 4” TIES**	25	**1/8 X 5-1/2” TIES**
3	**38956**	4	**12078**
25	**3/16 X 7-1/2” TIES**	25	**3/16 X 7-1/2” TIES WITH MOUNTING HOLE**
5	**38953**		
25	**3/16 X 11” TIES**		
6	**38957**		
25	**3/16 X 14” TIES**		
7	**38958**		
15	**5/16 X 14” HEAVY DUTY**		
8	**38958**		
15	**5/16 X 14” HEAVY DUTY**		

J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART # 2186

BLACK CABLE TIES

1	**38950**	25 — **3/32 X 3-3/4” TIES**
2	**38945**	25 — **1/8 X 5-1/2” TIES**
3	**38959**	25 — **3/16 X 7” TIES**
4	**12078**	25 — **3/16 X 7-1/16” WHITE TIES WITH MOUNTING HOLE**
5	**38947**	25 — **3/16 X 11” TIES**
6	**38951**	25 — **3/16 X 14-1/4” TIES**
7	**38946**	25 — **7/32 X 5-1/2” RELEASABLE**
8	**38954**	15 — **5/16 X 14” HEAVY DUTY**



J&B Fleet - Industrial Supply

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com

PART# 2288

BLACK CABLE TIES

38954



25 — 5/16 X 14**" TIES**

38954



25 — 5/16 X 14**" TIES**

38951

25 — 3/16 X 14**" TIES**

38947

25 — 3/16 X 11**" TIES**

38959

25 — 3/16 X 7**" TIES**

38945

25 — 1/8 X 5**" TIES**

40027

15 — NYLON TIE MOUNT BLACK ADHESIVE CABLE TIE MOUNTS

J&B Fleet - Industrial Supply
22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411
www.jbfleet.com

PART # 2187

COLORED CABLE TIES

38956 25 **3/16 X 7-1/2 WHITE**	**38959** 25 **3/16 X 7-1/2 BLACK**
41913 25 **3/16 X 7-1/2 BROWN**	**41914** 25 **3/16 X 7-1/2 RED**
41915 25 **3/16 X 7-1/2 ORANGE**	**41916** 25 **3/16 X 7-1/2 YELLOW**
41917 25 **3/16 X 7-1/2 GREEN**	**41918** 25 **3/16 X 7-1/2 BLUE**
41919 25 **3/16 X 7-1/2 PURPLE**	**41921** 25 **3/16 X 7-1/2 NEON PINK**

LET US HELP YOU MAKE THE CONNECTION

PART# 3105

COLOR TIE ASSORTMENT

J & B FLEET-INDUSTRIAL SUPPLY
PHONE: 330-821-6342

86121 3/32 X 4 41914 3/16 X 7.5	86122 3/32 X 4 41915 3/16 X 7.5	86123 3/32 X 4 41916 3/16 X 7.5	86124 3/32 X 4 41917 3/16 X 7.5	86125 3/32 X 4 41918 3/16 X 7.5	86126 3/32 X 4 41919 3/16 X 7.5
					
25	25	25	25	25	25

LET US HELP YOU MAKE THE CONNECTION

PART# 3097

COLOR CABLE TIES

J & B FLEET-INDUSTRIAL SUPPLY
PHONE: 330-821-6342

86121	86122	86123	86124	86125	86126
RED	ORANGE	YELLOW	GREEN	BLUE	PURPLE
3/32 X 4	3/32 X 4	3/32 X 4	3/32 X 4	3/32 X 4	3/32 X4
50	50	50	50	50	50