**Automatic Scrubbers** 

**CT 70** 



19/20 Gallon, 20, 24, 28" - Brush and Traction Drive

### **High Productivity**



Large solution capacity in a minimum external space



Extensive running time, large battery compartment



Solution Control with automatic stop



Available in brush or traction drive (BT version)



Brush Control with delayed automatic stop









**CT 70** 





#### **High Performance**



CFS (Center Flow System)
Solution distribution from
brush center



CWS (Constant Weight System) Ensures maximum scrubbing results



Exclusive squeegee system assures high performance at low cost



High quality / high performance vacuum motor

### Ergonomics, User Friendly



Great maneuverability due to optimum weight distribution



Great working visibility



Designed to assure Minimum noise levels



Easy to use control panel



Battery level indicator



Recovery tank discharge hose at maximum height



Recovery tank can be tilted for ease of cleaning



On board charger



External battery charger plug

#### Low Maintenance Costs



Inlet and outlet filters for maximum solution tank protection



AFS (Anti Foam System) and shut off sensor protect vacuum



Spin-on spin-off brush/pad driver (single brush only)



Squeegee blade can be used on 4 sides before replacement



Squeegee assembly and blade replacement without tools



Easy access to internal compartments





#### **Automatic Scrubbers**







### Durability



Tanks and surrounding body in high density polyethylene



Oil bath reduction gear box



Brush head designed to absorb harsh impact



Squeegee system designed to absorb harsh impact



Panel control switches protected against water and humidity









Technical Data		B 50	BT 50	BT 60	BT 70
Drive System		Brush	Traction	Traction	Traction
Scrubbing width	Inches/mm.	20"/500 mm	20"/500 mm	24"/600 mm	28"/700 mm
Squeegee width	Inches/mm.	32"/815 mm	32"/815 mm	32"/815 mm	40"/1010 mm
No. of brushes		1 (disc)	1 (disc)	2 (disc)	2 (disc)
Solution tank capacity	Gal/Ltr	19 Gal/75 Ltr	19 Gal/75 Ltr	19 Gal/75 Ltr	19 Gal/75 Ltr
Recovery tank capacity	Gal/Ltr	20 Gal/75 Ltr	20 Gal/75 Ltr	20 Gal/75 Ltr	20 Gal/75 Ltr
Battery power supply	Volts/Amp Hours Battery power supply	24V 145/155 Ah	24V 145/155 Ah	24V 145/155 Ah	24V 145/155 Ah
Empty weight without batt.	Lbs/Kg	154 Lbs/70 Kg	155 Lbs/70 Kg	194 Lbs/88 Kg	194 Lbs/88 Kg
Length	Inches/mm.	48"/1215 mm	48"/1215 mm	48"/1210 mm	48"/1220 mm
Width	Inches/mm.	21"/543mm	21"/543 mm	27"/680 mm	29.5"/748 mm
Height	Inches/mm.	38"/960 mm	38"/960 mm	38"/960 mm	38"/960 mm
Electro-valve solution flow		Yes	Yes	Yes	Yes
Electric traction			Yes	Yes	Yes
Max speed	Mph/Kmh	2.2 Mph/3.5 Kmh	2.8 Mph/4.5 Kmh	2.8 Mph/4.5 Kmh	2.8 Mph/4.5 Kmh



#### **Automatic Scrubbers**

**CT 70** 





#### **Competitive Advantages**



## **Exclusive squeegee system assures** high performance

Incomparable drying results even on the most difficult surfaces due to a very unique design.



## Maximum protection for the vacuum motor (water level sensor)

- 1. The vacuum motor is mounted in the highest part of the machine and is protected by a filter and water level sensor.
- 2. When the recovery tank is full, the left LED lights up and the vacuum motor shuts down. The right LED indicates when the cleaning solution has reached the reserve and there is enough solution for about two minutes.



# Large tank capacity in minimum external space

19/20 Gal (70-75 Ltr) capacity makes this model very unique in its category.



### Brush control with automatic delayed stop

Saves brush wear and protects the floor surface. Brush rotation stops (3 sec. delay on traction drive) and starts upon brush activation.



### Solution control with automatic stop

Saves water and chemicals. Solution flow stops and stars upon brush activation.



#### Recovery tank can be tilted

Easy to rinse and clean with smooth internal finishes.



IPC Eagle Corporation Sales and Service Provided By: